ETM60 TUBE BENDER

- entirely made of steel, sturdy, precise and fast
- max tube bending capacity:Ø 60 mm tube with 4 mm thickness
- o completely run and aided by an incorporated microprocessor which allows to store up to 40 different programmes, each of them with a 5-stop sequence in the bending operation
- minimum bending radius: 3 times the \emptyset of the tube (varies according to the tube wall thickness and material)

o weight: 190 kg











ATTENZIONE E

MAXIMUM BENDING CAPACITY		
Boiler tube	60 x 4	2″ gas x 0.1 <i>57</i> ″
Hydraulic steel	48 x 4	1½" x 0.203"
Aluminium	60 x 8	2" x 0.300"
Round bar (mild steel)	40	11/4"
Square tube (mild steel)	40 x 40 x 4	$1\frac{1}{4}$ " x $\frac{1}{4}$ " x 0.203"

TECHNICAL DATA

Drive motor KW 2 400/240 V - Rotation speed = 3 revolutions per minute (50Hz) Gear reduction driven in oil - Electronic device for angle control Approximative weight: 190 Kg - Dimensions mm: base 600x500 height 980

All specifications may be subject to change without notice



MEMOLI s.a.s. - via Magellano, 13 - 20049 Concorezzo - Mi - Italy Tel. ++39 039 6042210 - Fax ++39 039 648437 www.memoli.it - memoli@tin.it